



CAST IRON SUMP PUMPS



- Automatic submersible operation for use in 14" diameter basins or greater.
- Clog resistant design capable of passing 1/2" diameter solids.
- Tethered float switch.
- Professional grade shaft seal.

1/2 HP - Part No. SC50T

| Outlet | Amps | Watts | Cord | Gallons per hour at height: | | | | | |
|------------|------|-------|-------|-----------------------------|------|-------|-------|-------|----------|
| | | | | 0 ft | 5 ft | 10 ft | 15 ft | 20 ft | Shut off |
| 1 1/2" FPT | 11.5 | 1250 | 10 ft | 4000 | 3720 | 3360 | 2760 | 2100 | 28 ft |



1/3 HP - Part No. SC33T

| Outlet | Amps | Watts | Cord | Gallons per hour at height: | | | | | |
|------------|------|-------|-------|-----------------------------|------|-------|-------|-------|----------|
| | | | | 0 ft | 5 ft | 10 ft | 15 ft | 20 ft | Shut off |
| 1 1/2" FPT | 9 | 750 | 10 ft | 3600 | 3120 | 2640 | 1800 | 480 | 21 ft |

THERMOPLASTIC SUMP PUMPS



- Automatic submersible operation for use in 14" diameter basins or greater.
- Corrosion and rust resistant.
- Tethered float switch.
- Water-cooled PSC motor.
- Professional grade shaft seal.

1/2 HP - Part No. SP50T

| Outlet | Amps | Watts | Cord | Gallons per hour at height: | | | | | |
|------------|------|-------|-------|-----------------------------|------|-------|-------|-------|----------|
| | | | | 0 ft | 5 ft | 10 ft | 15 ft | 20 ft | Shut off |
| 1 1/2" FPT | 5 | 540 | 10 ft | 3500 | 3180 | 2640 | 2100 | 1200 | 26 ft |



1/3 HP - Part No. SP33T

| Outlet | Amps | Watts | Cord | Gallons per hour at height: | | | | | |
|------------|------|-------|-------|-----------------------------|------|-------|-------|-------|----------|
| | | | | 0 ft | 5 ft | 10 ft | 15 ft | 20 ft | Shut off |
| 1 1/2" FPT | 3.3 | 380 | 10 ft | 2850 | 2400 | 1900 | 1300 | 360 | 22 ft |

CAST IRON SEWAGE PUMP



- Automatic submersible operation for use in 18" diameter basins or greater.
- Ideal for high volume sewage, effluent and wastewater removal needs.
- Clog resistant design capable of passing 2" diameter solids.
- Tethered float switch.
- Professional grade shaft seal.

4/10 HP - Part No. WC50TA

| Outlet | Amps | Watts | Cord | Gallons per hour at height: | | | | |
|--------|------|-------|-------|-----------------------------|------|-------|-------|----------|
| | | | | 0 ft | 5 ft | 10 ft | 15 ft | Shut off |
| 2" FPT | 13 | 1020 | 15 ft | 6600 | 4800 | 3000 | 960 | 18 ft |

MULTI-PURPOSE PUMP

- Submersible epoxy-coated cast aluminum pump.
- Ideal for emergency water removal or water transfer situations.
- Screened bottom intake design.
- Thermally protected motor.
- Includes 3/4" garden hose adapter.



1/6 HP - Part No. MPA16A

| Outlet | Amps | Watts | Cord | Gallons per hour at height: | | | | |
|--------|------|-------|-------|-----------------------------|------|-------|-------|----------|
| | | | | 0 ft | 5 ft | 10 ft | 15 ft | Shut off |
| 1" FPT | 5 | 380 | 10 ft | 1200 | 1100 | 1000 | 840 | 26 ft |

ELECTRIC PRESSURE WASHERS



Motor1 phase 110V (2.0 hp)
Pump Comet BXD2020E
GPM 2.0
PSI 1500
Amps17
Weight94 lbs.
 • Switch, cord and plug included.
 • 25' Steel wire braided hose
 • Industrial spray gun
 • Powder coated steel frame
 • 0°, 15° & 40° Quick connect nozzles & soap nozzle

2 HP - Part No. X-1520EW1COMX



Motor1 phase 220V (7.5 hp)
Pump Comet FWS3530E
GPM 3.5
PSI 2700
Amps32
Weight219 lbs.
 • 50' Steel wire braided hose
 • Industrial 5000 PSI spray gun
 • Powder coated steel frame
 • Low pressure chemical injector
 • 0°, 15° & 40° Quick connect nozzles & soap nozzle
 * Does not include cord, switch or plug.*

7.5 HP - Part No. PE-2775EW1COM

SOAP DETERGENTS - 1 GALLON

Car Wash



No. 85.490.050

House & Siding



No. 85.490.051

Deck & Fence



No. 85.490.052

Heavy Duty Degreaser



No. 85.490.053

SOAP DETERGENTS - 5 GALLON



| No. | Description |
|------------|----------------------|
| 85.490.055 | Car Wash |
| 85.490.056 | House & Siding |
| 85.490.057 | Deck & Fence |
| 85.490.058 | Heavy Duty Degreaser |

SOAP HOLDER



Affixes to the frame for convenient storage of 1 gallon containers

No. 85.601.010

PUMP OIL



- Reduces scuff and wear in piston and plunger pumps
- Inhibits moisture that causes damage
- For use with plunger, piston and diaphragm pumps.
- 1 Liter

Part No. 2214

PUMP SAVER ANTI-FREEZE

- Attaches to any pump inlet to fill pump chamber with anti-freeze solution.



Part No. 85.490.042



PRESSURE WASHERS



GAS POWERED PRESSURE WASHERS



EngineHonda GC160 (5.0 hp)
PumpAxial
GPM2.1
PSI2500
Weight71 lbs.

- EZ-Grip garden hose fittings.
- 25' Steel wire braided hose
- 2950 PSI Front entry spray gun
- 36" insulated lance
- 0°, 15° & 40° Quick connect nozzles & soap nozzle

**5 HP Direct Drive Unit -
Part No. X-2005HWX**



EngineHonda GC190 (5.0 hp)
PumpComet BXD2528G
GPM2.5
PSI2800
Weight90 lbs.

- EZ-Grip garden hose fittings.
- 50' Steel wire braided hose
- 2950 PSI Front entry spray gun
- 36" insulated lance
- 0°, 15° & 40° Quick connect nozzles & soap nozzle

**6 HP Direct Drive Unit -
Part No. X-2760HWCMBH**



EngineHonda GX200 (6.5 hp)
PumpComet BWDK3027G
GPM3.0
PSI2700
Weight93 lbs.

- 25' Steel wire braided hose
- 2950 PSI Front entry spray gun
- 36" insulated lance
- 0°, 15° & 40° Quick connect nozzles & soap nozzle

**6.5 HP Direct Drive Unit -
Part No. X-2565HWCOM**



EngineHonda GX390 (13 hp)
PumpComet ZWDK4036
GPM4.0
PSI3600
Weight158 lbs.

- 25' Steel wire braided hose
- 5000 PSI Industrial spray gun
- Thermal relief valve
- 36" insulated lance
- 0°, 15° & 40° Quick connect nozzles & soap nozzle

**13 HP Direct Drive Unit -
Part No. X-4013HWPCOMK**

HOT WATER PRESSURE WASHER



EngineHonda GX390 Series OHV (13 hp)
PumpAR Triplex pump with
ceramic plungers
GPM4.0
PSI3500
Weight428 lbs.

- 50' pressure hose with viton QD
- 36" gun and wand assembly
- 0°, 15° & 40° Quick connect nozzles & 50° soap nozzle
- Powder coated frame
- EMF (electroy magneto fired) burner

**13 HP Gas Powered Unit -
Part No. X-HW3513AR**

BRUSH ATTACHMENTS

**Rotating Nylon Brush -
Part No. 85.400.008**

- Max 2000 PSI
- 140° F Max
- 1/4" QC or Male M22 Inlet



**Fixed Nylon Brush -
Part No. 85.400.040**

- Max 3000 PSI
- 140° F Max
- Female M22 Inlet



**Telescoping Car Wash Brush -
Part No. 85.400.043**

- Extends to 6½" ft
- 3/4" FGHT Inlet



ADJUSTABLE WATER NOZZLES



- 6 way adjustable head
- 5/2" zinc alloy nozzle
- Insulated handle

Part No. 3410



- Adjustable brass head
- 5/2" zinc alloy nozzle
- Insulated handle

Part No. 3411



- Adjustable head
- 5/2" zinc alloy nozzle
- Insulated handle

Part No. 3409

RUBBER WATER HOSE



GREEN GARDEN HOSE

- 50 ft 1/2" ID superflex hose
- Stays flexible at -40°C
- 300 PSI @ 70°F

Part No. 2990



BLACK GARDEN HOSE

- 50 ft 5/8" ID superflex hose

Part No. 2991

GARDEN HOSE VALVES



**NYLON "Y"
BALL VALVE**

FGHT x (2) MGHT

| No. | Size |
|------|-------------|
| 5181 | 3/4" x 3/4" |



**NYLON BALL
VALVE**

FGHT x MGHT

| No. | Size |
|------|-------------|
| 5180 | 3/4" x 3/4" |

GARDEN HOSE QUICK COUPLERS



| No. | Description |
|------|--|
| 5182 | 3/4" FGHT x 3/4" Male Adapter w/ Shutoff |
| 5183 | 3/4" FGHT x 3/4" Male Adapter |
| 5184 | 3/4" MGHT x 3/4" Female Adapter |
| 5185 | 3/4" FGHT x 3/4" Female Coupler |
| 5186 | 3/4" MGHT x 3/4" Male Adapter |
| 5187 | 3/4" Female Coupler x 3/4" Male Adapter w/ Shutoff |
| 5188 | 3/4" FGHT x 3/4" Male Adapter w/ Timer |

CAPS & PLUGS

FGHT CAPS



NYLON

| No. | Size |
|-------|------|
| 50-34 | 3/4" |



POLY

| No. | Size |
|--------|------|
| 50-34P | 3/4" |



BRASS

| No. | Size |
|--------|------|
| 50-34B | 3/4" |

MGHT PLUGS



BRASS

| No. | Size |
|--------|------|
| 57-34B | 3/4" |

ADAPTERS

MGHT x HB



NYLON

| No. | Size |
|---------|-------------|
| 40-3414 | 3/4" x 1/4" |
| 40-3438 | 3/4" x 3/8" |
| 40-3412 | 3/4" x 1/2" |
| 40-3458 | 3/4" x 5/8" |
| 40-34 | 3/4" x 3/4" |



POLY

| No. | Size |
|----------|-------------|
| 40-3414P | 3/4" x 1/4" |
| 40-3438P | 3/4" x 3/8" |
| 40-3412P | 3/4" x 1/2" |
| 40-3458P | 3/4" x 5/8" |
| 40-34P | 3/4" x 3/4" |



BRASS

| No. | Size |
|---------|-------------|
| 40-38B | 3/4" x 3/8" |
| 40-12B | 3/4" x 1/2" |
| 40-58B | 3/4" x 5/8" |
| 40-34B | 3/4" x 3/4" |
| 40-100B | 1" x 1" |



**ZINC PLATED
STEEL**

| No. | Size |
|-----------|-------------|
| 40-3438SP | 3/4" x 3/8" |
| 40-3412SP | 3/4" x 1/2" |
| 40-34SP | 3/4" x 3/4" |

FGHT x MPT



NYLON

| No. | Size |
|-------|-------------|
| 46-34 | 3/4" x 3/4" |



POLY

| No. | Size |
|--------|-------------|
| 46-34P | 3/4" x 3/4" |



BRASS

| No. | Size |
|--------|-------------|
| 46-38B | 3/4" x 3/8" |
| 46-12B | 3/4" x 1/2" |
| 46-34B | 3/4" x 3/4" |

MGHT x FPT



NYLON

| No. | Size |
|-------|-------------|
| 43-14 | 3/4" x 1/4" |
| 43-12 | 3/4" x 1/2" |
| 43-34 | 3/4" x 3/4" |



POLY

| No. | Size |
|--------|-------------|
| 43-14P | 3/4" x 1/4" |
| 43-12P | 3/4" x 1/2" |
| 43-34P | 3/4" x 3/4" |



BRASS

| No. | Size |
|--------|-------------|
| 43-14B | 3/4" x 1/4" |
| 43-38B | 3/4" x 3/8" |
| 43-12B | 3/4" x 1/2" |
| 43-34B | 3/4" x 3/4" |

FGHT x MGHT



NYLON

| No. | Size |
|-------|-------------|
| 47-34 | 3/4" x 3/4" |



POLY

| No. | Size |
|--------|-------------|
| 47-34P | 3/4" x 3/4" |

WASHERS



**GARDEN
HOSE
WASHER**

| No. | Size |
|------|----------------------|
| 1712 | 3/4" Washer |
| 1713 | 3/4" Filter / Washer |
| 1716 | 1" Washer |

SWIVEL ADAPTERS

FPT / FGHT x HB



NYLON

| No. | Hose Barb | Nut Req |
|-------------|-----------|---------|
| 34-14 | 1/4" | 3/4" |
| 34-38 | 3/8" | 3/4" |
| 34-12 | 1/2" | 3/4" |
| 34-58 | 5/8" | 3/4" |
| 34-34 | 3/4" | 3/4" |
| 34-100 | 1" | 1" |
| Swivel Nuts | | |
| 36-34 | 3/4" FPT | |
| 38-34 | 3/4" FGHT | |
| 36-100 | 1" FPT | |



POLY

| No. | Hose Barb | Nut Req |
|-------------|-----------|---------|
| 34-14P | 1/4" | 3/4" |
| 34-38P | 3/8" | 3/4" |
| 34-12P | 1/2" | 3/4" |
| 34-58P | 5/8" | 3/4" |
| 34-34P | 3/4" | 3/4" |
| 34-100P | 1" | 1" |
| Swivel Nuts | | |
| 36-34 | 3/4" FPT | |
| 38-34 | 3/4" FGHT | |
| 36-100 | 1" FPT | |



POLY BALL SEAT

| No. | Hose Barb | Nut Req |
|----------|-----------|---------|
| 65-14P | 1/4" | 1/4" |
| 65-1412P | 1/4" | 1/2" |
| 65-38P | 3/8" | 3/8" |
| 65-12P | 1/2" | 1/2" |
| Hex Nuts | | |
| 66-14P | 1/4" FPT | |
| 66-38P | 3/8" FPT | |
| 66-12P | 1/2" FPT | |

ELBOWS

MGHT x HB



NYLON

| No. | Size |
|---------|-------------|
| 41-3414 | 3/4" x 1/4" |
| 41-3438 | 3/4" x 3/8" |
| 41-3412 | 3/4" x 1/2" |
| 41-3458 | 3/4" x 5/8" |
| 41-34 | 3/4" x 3/4" |



POLY

| No. | Size |
|----------|-------------|
| 41-3414P | 3/4" x 1/4" |
| 41-3438P | 3/4" x 3/8" |
| 41-3412P | 3/4" x 1/2" |
| 41-3458P | 3/4" x 5/8" |
| 41-34P | 3/4" x 3/4" |



BRASS
(Nut Included)

| No. | FPT x HB |
|--------|-------------|
| 72-38B | 3/4" x 3/8" |
| 72-12B | 3/4" x 1/2" |
| 72-58B | 3/4" x 5/8" |
| 72-34B | 3/4" x 3/4" |

| No. | FGHT x HB |
|--------|-------------|
| 70-38B | 3/4" x 3/8" |
| 70-12B | 3/4" x 1/2" |
| 70-58B | 3/4" x 5/8" |
| 70-34B | 3/4" x 3/4" |



BRASS NUTS

| No. | Description |
|--------|-----------------|
| 38-34B | 3/4" FGHT Knurl |
| 37-34B | 3/4" FGHT Hex |
| 36-34B | 3/4" FPT Hex |



ZINC PLATED STEEL

| No. | Hose Barb | Nut Req |
|-------------|-----------|---------|
| 34-38SP | 3/8" | 3/4" |
| 34-12SP | 1/2" | 3/4" |
| 34-58SP | 5/8" | 3/4" |
| 34-34SP | 3/4" | 3/4" |
| Swivel Nuts | | |
| 36-34SP | 3/4" FPT | |
| 38-34SP | 3/4" FGHT | |

FGHT x MPT



BRASS

| No. | Size |
|--------|-------------|
| 60-14B | 3/4" x 1/4" |
| 60-38B | 3/4" x 3/8" |
| 60-12B | 3/4" x 1/2" |

NIPPLES

MGHT x MGHT



NYLON

| No. | Size |
|-------|-------------|
| 48-34 | 3/4" x 3/4" |



POLY

| No. | Size |
|--------|-------------|
| 48-34P | 3/4" x 3/4" |



BRASS

| No. | Size |
|--------|-------------|
| 48-34B | 3/4" x 3/4" |

MGHT x MPT



NYLON

| No. | Size |
|---------|-------------|
| 39-3438 | 3/4" x 3/8" |
| 39-3412 | 3/4" x 1/2" |
| 39-34 | 3/4" x 3/4" |



POLY

| No. | Size |
|----------|-------------|
| 39-3438P | 3/4" x 3/8" |
| 39-3412P | 3/4" x 1/2" |
| 39-34P | 3/4" x 3/4" |



BRASS

| No. | Size |
|-----------|-------------|
| 56-38B | 3/4" x 3/8" |
| 56-12B | 3/4" x 1/2" |
| 56-34B | 3/4" x 3/4" |
| 56-100B | 3/4" x 1" |
| 56-1-100B | 1" FPT x 1" |

TEES

MGHT x HB



NYLON

| No. | Size |
|-------|-------------|
| 42-38 | 3/4" x 3/8" |
| 42-12 | 3/4" x 1/2" |
| 42-58 | 3/4" x 5/8" |
| 42-34 | 3/4" x 3/4" |

COUPLINGS

FGHT x FPT



NYLON

| No. | Size |
|-------|-------------|
| 58-12 | 3/4" x 1/2" |
| 58-34 | 3/4" x 3/4" |



POLY

| No. | Size |
|--------|-------------|
| 58-12P | 3/4" x 1/2" |
| 58-34P | 3/4" x 3/4" |



BRASS

| No. | Size |
|--------|-------------|
| 58-18B | 3/4" x 1/8" |
| 58-14B | 3/4" x 1/4" |
| 58-38B | 3/4" x 3/8" |
| 58-12B | 3/4" x 1/2" |
| 58-34B | 3/4" x 3/4" |



BRASS SWIVEL

| No. | Size |
|--------|-------------|
| 49-12B | 3/4" x 1/2" |
| 49-34B | 3/4" x 3/4" |

FGHT x FGHT



BRASS

| No. | Size |
|--------|-------------|
| 67-34B | 3/4" x 3/4" |



BRASS SWIVEL

| No. | Size |
|--------|-------------|
| 55-34B | 3/4" x 3/4" |



"Y" COUPLING
FGHT x (2) MGHT

| No. | Size |
|--------|--------------------|
| 61-34B | 3/4" x 3/4" x 3/4" |

CONNECTING PEX TUBE TO BRASS INSERT FITTINGS

1. Cut Pex pipe squarely. Check pipe I.D. and O.D. and remove any burrs.
2. Apply copper ring or PEX clamp on top of PEX pipe.
3. Insert fitting into the end of the pipe and pull clamp or ring over the fitting within 1/8 to 1/4 inch from the end of the tube. This process presses the fitting ribs into the pipe.
4. Crimp copper ring or PEX clamp using the required Fairview tool.
5. Check crimp using the Go-No-Go Gauge to determine if the crimp connection was properly made.
6. The GO opening should go freely across a crimped ring. The No-Go opening should not go across a crimped ring.



STEP 1



STEP 2



STEP 3



STEP 4



STEP 5



STEP 6

PEX FITTING FIELD KITS



Part No. PEX-KIT-BCR

| Kit Includes: (Qty) | |
|---------------------|-------------------|
| PEX-99HB-10 (2) | PEX-126-14E (2) |
| PEX-99HB-14 (2) | PEX-126SW-10 (2) |
| PEX-121HB-10 (2) | PEX-126SW-14 (2) |
| PEX-121HB-14 (2) | PEX-129-10 (2) |
| PEX-123-10 (1) | PEX-129-14 (2) |
| PEX-123-14 (1) | PEX-S139F-10D (1) |
| PEX-125-10D (2) | PEX-S139F-14E (1) |
| PEX-125-10E (2) | BVPEX2129-10 (1) |
| PEX-125-14D (2) | BVPEX2129-14 (1) |
| PEX-125-14E (2) | HCPEX-10-BCR (10) |
| PEX-125SW-10 (2) | HCPEX-14-BCR (10) |
| PEX-125SW-14 (2) | HCPEX-GNG (1) |
| PEX-126-10D (2) | PEX-JC-10 (10) |
| PEX-126-10E (2) | PEX-JC-14 (10) |



Part No. PEX-KIT-HC

| Kit Includes: (Qty) | |
|---------------------|-------------------|
| PEX-99HB-10 (2) | PEX-126-14E (2) |
| PEX-99HB-14 (2) | PEX-126SW-10 (2) |
| PEX-121HB-10 (2) | PEX-126SW-14 (2) |
| PEX-121HB-14 (2) | PEX-129-10 (2) |
| PEX-123-10 (1) | PEX-129-14 (2) |
| PEX-123-14 (1) | PEX-S139F-10D (1) |
| PEX-125-10D (2) | PEX-S139F-14E (1) |
| PEX-125-10E (2) | BVPEX2129-10 (1) |
| PEX-125-14D (2) | BVPEX2129-14 (1) |
| PEX-125-14E (2) | HCPEX-10 (10) |
| PEX-125SW-10 (2) | HCPEX-14 (10) |
| PEX-125SW-14 (2) | HCPEX-GNG (1) |
| PEX-126-10D (2) | PEX-JC-10 (10) |
| PEX-126-10E (2) | PEX-JC-14 (10) |

ACCUTEK PEX TUBING

Pressure Rating: 160 PSI @ 73°F (23°C)
 100 PSI @ 180°F (82°C)
 80 PSI @ 200°F (93.3°C)

PEX Non-barrier tube is manufactured without an EVOH coating and may be used in heating systems without ferrous metal components, or where ferrous metals are isolated from the tube with a heat exchanger.
 Sold in coils



WHITE TUBING



RED TUBING

| No. | O.D. | Wall | Coil |
|------------|------|------|--------|
| PNB-10-100 | 1/2" | .062 | 100 ft |
| PNB-10-300 | 1/2" | .062 | 300 ft |
| PNB-14-100 | 3/4" | .097 | 100 ft |
| PNB-14-300 | 3/4" | .097 | 300 ft |

| No. | O.D. | Wall | Coil |
|---------------|------|------|--------|
| PNB-10RED-100 | 1/2" | .062 | 100 ft |
| PNB-10RED-300 | 1/2" | .062 | 300 ft |
| PNB-14RED-100 | 3/4" | .097 | 100 ft |
| PNB-14RED-300 | 3/4" | .097 | 300 ft |



WHITE STRAIGHT LENGTHS

| No. | O.D. | Wall | Length |
|-------------|------|------|--------|
| PNB-10-20HL | 1/2" | .083 | 20 ft |
| PNB-14-20HL | 3/4" | .097 | 20 ft |



BRASS PEX FITTINGS & ACCESSORIES



PEX FITTINGS

TOOLS



ADAPTER
Pex to MPT

| No. | Pex | MPT |
|-------------|------|------|
| PEX-125-10D | 1/2" | 1/2" |
| PEX-125-10E | 1/2" | 3/4" |
| PEX-125-14E | 3/4" | 3/4" |
| PEX-125-14D | 3/4" | 1/2" |



ADAPTER
Pex to Male Sweat

| No. | Pex | Tube |
|--------------|------|-------|
| PEX-125SW-10 | 1/2" | 1/2 K |
| PEX-125SW-14 | 3/4" | 3/4 K |



ADAPTER
Pex to FPT

| No. | Pex | FPT |
|-------------|------|------|
| PEX-126-10D | 1/2" | 1/2" |
| PEX-126-14E | 3/4" | 3/4" |



ADAPTER
Pex to FPT Swivel

| No. | Pex | FPT |
|----------------|------|------|
| PEX-126SPN-10D | 1/2" | 1/2" |
| PEX-126SPN-14E | 3/4" | 3/4" |



ADAPTER
Pex to Female Sweat

| No. | Pex | Tube |
|--------------|------|-------|
| PEX-126SW-10 | 1/2" | 1/2 K |
| PEX-126SW-14 | 3/4" | 3/4 K |



ADAPTER
Pex to Pex

| No. | Pex | MPT |
|--------------|------|------|
| PEX-129-10 | 1/2" | 1/2" |
| PEX-129-14 | 1/2" | 3/4" |
| PEX-129-1410 | 3/4" | 3/4" |



PEX PLUG

| No. | Pex |
|--------------|------|
| PEX-121HB-10 | 1/2" |
| PEX-121HB-14 | 3/4" |



90° ELBOW
Pex to Pex

| No. | Pex | Pex |
|-------------|------|------|
| PEX-99HB-10 | 1/2" | 1/2" |
| PEX-99HB-14 | 3/4" | 3/4" |



FLANGED 90° ELBOW
Pex to FPT

| No. | Pex | FPT |
|---------------|------|------|
| PEX-S139F-10D | 1/2" | 1/2" |
| PEX-S139F-14E | 3/4" | 3/4" |




90° ELBOW
Pex to FPT Swivel

| No. | Pex | FPT |
|-----------------|------|------|
| PEX-139FSPN-10D | 1/2" | 1/2" |
| PEX-139FSPN-14E | 3/4" | 3/4" |



TEE
Pex

| No. | Pex | Pex |
|------------|------|------|
| PEX-123-10 | 1/2" | 1/2" |
| PEX-123-14 | 3/4" | 3/4" |



REDUCING TEE
Pex

| No. | Pex | Pex | Pex |
|----------------|------|------|------|
| PEX-123-1014 | 1/2" | 1/2" | 3/4" |
| PEX-123-1410 | 3/4" | 3/4" | 1/2" |
| PEX-123-141010 | 3/4" | 1/2" | 1/2" |
| PEX-123-141014 | 3/4" | 1/2" | 3/4" |

VALVES



FORGED BRASS BALL VALVE

- Double viton o-ring
- Blow-out proof stem
- 400 WOG

| No. | Pex |
|--------------|------|
| BVPEX2129-10 | 1/2" |
| BVPEX2129-14 | 3/4" |

CRIMP TOOL KIT



• 14" Hand crimp tool kit for crimping black copper rings on 3/8", 1/2", 5/8" and 3/4" pex. Kit includes replaceable jaws for all sizes and Go-No-Go gauge.

Part No. HCPEX-RTC-KIT



CLAMP TOOL

Part No. HCPEX-RTE



OETIKER CLAMP TOOL

Part No. HCPEX-RT



CRIMP RING REMOVING CUTTER

Part No. HCPEX-CRC



PEX ANGLE CRIMP TOOL

| No. | Pex |
|---------------|------|
| HCPEX-RTAC-10 | 1/2" |
| HCPEX-RTAC-14 | 3/4" |



TUBE & PEX PIPE CUTTER

Part No. MCE-1

TUBE SUPPORTS



BEND SUPPORT

| No. | Pex |
|-----------|------|
| PEX-BS-10 | 1/2" |
| PEX-BS-14 | 3/4" |



J-CLAMP (With Nail)

| No. | Pex |
|-----------|------|
| PEX-JC-10 | 1/2" |
| PEX-JC-14 | 3/4" |

CLAMPS & CRIMP RINGS



STAINLESS STEEL STEPLESS CLAMP

| No. | Pex |
|----------|------|
| HCPEX-10 | 1/2" |
| HCPEX-14 | 3/4" |



BLACK COPPER CRIMP RING

| No. | Pex |
|--------------|------|
| HCPEX-10-BCR | 1/2" |
| HCPEX-14-BCR | 3/4" |

CEMENTS, PRIMERS & CLEANERS

PVC CEMENT

- For use on all grades & types of PVC and fittings up to 6".
- Recommended for gas, conduit, drain, waste & vent pipe.



MEDIUM CLEAR

| No. | Size |
|-------|-----------------|
| 5990C | 118 ml (4 oz.) |
| 5991C | 236 ml (8 oz.) |
| 5992C | 473 ml (16 oz.) |
| 5993C | 946 ml (32 oz.) |



MEDIUM GREY

| No. | Size |
|-------|-----------------|
| 5990G | 118 ml (4 oz.) |
| 5991G | 236 ml (8 oz.) |
| 5992G | 473 ml (16 oz.) |
| 5993G | 946 ml (32 oz.) |



**RAIN-R-SHINE[®]
MEDIUM BLUE**

- Fast setting cement for wet conditions (pools/irrigation), pressurization or quick installations.

| No. | Size |
|-------|-----------------|
| 5990R | 118 ml (4 oz.) |
| 5991R | 236 ml (8 oz.) |
| 5992R | 473 ml (16 oz.) |
| 5993R | 946 ml (32 oz.) |

CPVC CEMENT



MEDIUM CLEAR

| No. | Size |
|--------|-----------------|
| 5990CP | 118 ml (4 oz.) |
| 5991CP | 236 ml (8 oz.) |
| 5992CP | 473 ml (16 oz.) |

ABS CEMENT



MEDIUM YELLOW

| No. | Size |
|-------|-----------------|
| 5990A | 118 ml (4 oz.) |
| 5991A | 236 ml (8 oz.) |
| 5992A | 473 ml (16 oz.) |
| 5993A | 946 ml (32 oz.) |

TRANSITION CEMENT



PVC to ABS WHITE

- Used for joining PVC to ABS on non-pressure transition joints.

| No. | Size |
|-------|-----------------|
| 5990T | 118 ml (4 oz.) |
| 5991T | 236 ml (8 oz.) |
| 5992T | 473 ml (16 oz.) |

PRIMERS & CLEANERS

- All purpose primers for PVC and CPVC pipe and fittings, all schedules and diameters.
- Removes surface dirt, grease and grime as well as softens pipe in preparation for cement.



CLEAR PRIMER

| No. | Size |
|-------|-----------------|
| 5995P | 118 ml (4 oz.) |
| 5996P | 236 ml (8 oz.) |
| 5997P | 473 ml (16 oz.) |
| 5998P | 946 ml (32 oz.) |



PURPLE PRIMER

Less aggressive than clear primer.

| No. | Size |
|--------|-----------------|
| 5995PP | 118 ml (4 oz.) |
| 5996PP | 236 ml (8 oz.) |
| 5997PP | 473 ml (16 oz.) |
| 5998PP | 946 ml (32 oz.) |



CLEAR CLEANER

For ABS, PVC, CPVC all schedules and diameters.

| No. | Size |
|-------|-----------------|
| 5995C | 118 ml (4 oz.) |
| 5996C | 236 ml (8 oz.) |
| 5997C | 473 ml (16 oz.) |
| 5998C | 946 ml (32 oz.) |

TEFLON TAPE



STANDARD

- For use with water, most chemicals, oxygen, gas, hydraulic and high pressure lines.

Part No. 5962



PLUMBERS

- Higher density than standard.

Part No. 5962P



GAS LINE

- For use with gas, natural gas, propane and butane lines.
- Full density; heaviest tape available.

Part No. 5962Y



OXYGEN

- For oxygen lines; will not support combustion.

Part No. 5962GR



STAINLESS

- For use on all stainless steel fittings
- Prevents galling, seizing & corrosion.

Part No. 5962SS



HIGH DENSITY

- No pigments or additives.
- Perfect where non-contamination standards are high.

Part No. 5962W

JOINT COMPOUNDS



GRAY COMPOUND

- For use on water, steam or air lines.
- Not for use on plastic threads.

| No. | Size |
|-------|---------------------|
| 5957M | 1 oz. tube |
| 5959M | 236 ml (8 oz.) can |
| 5960M | 473 ml (16 oz.) can |
| 5961M | 946 ml (32 oz.) can |



WHITE COMPOUND WITH TEFLON

- For use with water, steam and caustics.
- Gases: 3000 PSI, -50°F to 400°F
- Liquids: 10000 PSI, -50°F to 500°F

| No. | Size |
|-------|---------------------|
| 5957T | 1 oz. tube |
| 5958T | 118 ml (4 oz.) can |
| 5959T | 236 ml (8 oz.) can |
| 5961T | 946 ml (32 oz.) can |



BLUE COMPOUND

- For use with water, natural gas, steam, air lines, caustics, and dilute acids on PVC, CPVC, ABS, poly, iron, steel or copper up to and including 2".
- Gases: 3000 PSI, -50°F to 400°F
- Liquids: 10000 PSI, -50°F to 500°F

| No. | Size |
|-------|---------------------|
| 5957B | 1 oz. tube |
| 5958B | 118 ml (4 oz.) can |
| 5959B | 236 ml (8 oz.) can |
| 5960B | 473 ml (16 oz.) can |
| 5961B | 946 ml (32 oz.) can |

SUPPLY LINES

STAINLESS STEEL TOILET SUPPLY LINES

• 3/8" Compression x 7/8" Toilet Connection



| No. | Length |
|---------|--------|
| 94TT-6 | 6" |
| 94TT-9 | 9" |
| 94TT-12 | 12" |
| 94TT-16 | 16" |
| 94TT-20 | 20" |

STAINLESS STEEL FAUCET SUPPLY LINES

• 3/8" Compression x 1/2" Female Thread Faucet Connection



| No. | Length |
|---------|--------|
| 93LT-12 | 12" |
| 93LT-16 | 16" |
| 93LT-20 | 20" |
| 93LT-30 | 30" |

STAINLESS STEEL DISHWASHER LINES

• 3/8" Compression x 3/8" Male Pipe Elbow Connection



| No. | Length |
|---------|--------|
| 95DW-48 | 48" |
| 95DW-60 | 60" |
| 95DW-72 | 72" |

STAINLESS STEEL WASHING MACHINE LINES

• 3/4" Female Hose x 3/4" Female Hose Connection



| No. | Length |
|---------|--------|
| 96WM-48 | 48" |
| 96WM-60 | 60" |
| 96WM-72 | 72" |

STAINLESS STEEL FEMALE CONNECTOR LINE

• 1/2" Female Thread x 1/2" Female Thread Connection



| No. | Length |
|----------|--------|
| 98FSL-12 | 12" |
| 98FSL-20 | 20" |

PLUMBING ACCESSORIES



BRASS PENCIL FLAME TORCH

- Produces 1/2" pencil flame
- Fuel control knob

Part No. 2317



SILVER LEAD FREE WIRE SOLDER

| No. | Size |
|------|--------|
| 5982 | 1/2 lb |
| 5983 | 1 lb |



ALL PURPOSE LEAK DETECTOR

| No. | Size |
|-------|---------------------|
| 5984L | 8 oz. with dauber |
| 5985L | 16 oz. with trigger |



EPOXY PUTTY

- Multi-purpose sealing, patching and mending compound.
- May be drilled, tapped, filed, sanded and painted when hard.

| No. | Size |
|------|----------------|
| 5956 | 118 ml (4 oz.) |



PROPANE CYLINDER

- In Store Only
- 14 oz.

Part No. 2318



180 OPEN MESH CLOTH

| No. | Size |
|--------|------------------|
| 5987-5 | 1 1/2" x 15 Feet |



HAND CLEANER

Safely removes cements, varnish, enamels, grease and adhesives.

| No. | Size |
|------|-----------------|
| 6002 | 473 ml (16 oz.) |



PLUMBERS PUTTY

Stainless fixture setting compound for setting frames, faucets, strainer baskets, etc.

| No. | Size |
|------|-----------------|
| 5974 | 414 ml (14 oz.) |

CLAMPS

HEAVY DUTY BOLT CLAMPS



- 430 Stainless Steel band with bevelled edge
- Zink Plated Bolt
- No. also represents range in millimeters

T-BOLT HOSE CLAMPS



- All Stainless Steel construction
- Ideal for high torque applications
- 360° sealing surface

GLOBAL "GS" SERIES



- Plated carbon steel hex head screw
- 301 stainless steel band & housing

GLOBAL "GS" 300 SS SERIES



- Screw 305 SS
- Band 301 SS
- Housing 301 SS

| No. | Diam. | Band |
|----------|---------------|--------|
| C17-19 | 0.67" - 0.75" | 0.708" |
| C19-21 | 0.75" - 0.83" | 0.708" |
| C21-23 | 0.83" - 0.91" | 0.708" |
| C23-25 | 0.91" - 0.98" | 0.708" |
| C25-27 | 0.98" - 1.06" | 0.708" |
| C27-29 | 1.06" - 1.14" | 0.708" |
| C29-31 | 1.14" - 1.22" | 0.787" |
| C31-34 | 1.22" - 1.34" | 0.787" |
| C34-37 | 1.34" - 1.46" | 0.787" |
| C37-40 | 1.46" - 1.57" | 0.787" |
| C40-43 | 1.57" - 1.69" | 0.787" |
| C43-47 | 1.69" - 1.85" | 0.787" |
| C47-51 | 1.85" - 2.01" | 0.787" |
| C51-55 | 2.01" - 2.17" | 0.787" |
| C55-59 | 2.17" - 2.32" | 0.787" |
| C59-63 | 2.32" - 2.48" | 0.787" |
| C63-68 | 2.48" - 2.68" | 0.984" |
| C68-73 | 2.68" - 2.87" | 0.984" |
| C73-79 | 2.87" - 3.11" | 0.984" |
| C79-85 | 3.11" - 3.35" | 0.984" |
| C85-91 | 3.35" - 3.58" | 0.984" |
| C91-97 | 3.58" - 3.82" | 0.984" |
| C97-104 | 3.82" - 4.09" | 0.984" |
| C104-112 | 4.09" - 4.41" | 0.984" |
| C112-121 | 4.41" - 4.76" | 0.984" |
| C121-130 | 4.76" - 5.12" | 0.984" |
| C131-139 | 5.16" - 5.47" | 1.024" |
| C140-148 | 5.51" - 5.83" | 1.024" |
| C149-161 | 5.87" - 6.34" | 1.024" |
| C162-174 | 6.38" - 6.85" | 1.024" |
| C175-187 | 6.89" - 7.36" | 1.024" |
| C188-200 | 7.40" - 7.87" | 1.024" |
| C201-213 | 7.91" - 8.39" | 1.024" |
| C214-226 | 8.43" - 8.90" | 1.024" |
| C227-239 | 8.94" - 9.41" | 1.024" |
| C240-252 | 9.45" - 9.92" | 1.024" |

| No. | Min. | Max . |
|------|--------|--------|
| 6576 | 1.38" | 1.56" |
| 6577 | 1.50" | 1.69" |
| 6578 | 1.62" | 1.81" |
| 6579 | 1.75" | 2.00" |
| 6580 | 1.88" | 2.13" |
| 6581 | 2.00" | 2.25" |
| 6582 | 2.13" | 2.38" |
| 6583 | 2.25" | 2.56" |
| 6584 | 2.38" | 2.69" |
| 6585 | 2.50" | 2.81" |
| 6586 | 2.63" | 2.94" |
| 6587 | 2.75" | 3.06" |
| 6588 | 2.88" | 3.15" |
| 6589 | 3.06" | 3.38" |
| 6590 | 3.25" | 3.56" |
| 6591 | 3.38" | 3.69" |
| 6592 | 3.56" | 3.88" |
| 6593 | 3.81" | 4.13" |
| 6594 | 4.06" | 4.38" |
| 6595 | 4.31" | 4.63" |
| 6596 | 4.56" | 4.88" |
| 6597 | 4.81" | 5.13" |
| 6598 | 5.06" | 5.38" |
| 6599 | 5.31" | 5.63" |
| 6600 | 5.56" | 5.88" |
| 6601 | 6.00" | 6.32" |
| 6602 | 6.25" | 6.56" |
| 6603 | 6.50" | 6.81" |
| 6604 | 6.75" | 7.06" |
| 6605 | 7.25" | 7.56" |
| 6606 | 7.75" | 8.06" |
| 6607 | 8.25" | 8.56" |
| 6608 | 9.25" | 9.56" |
| 6609 | 10.25" | 10.56" |

| No. | Size | Min. | Max. |
|---------------------------------|---------|---------|---------|
| Mini Clamp 3/8" Band 1/4" Screw | | | |
| HF-4 | 1/4" | 1/4" | 5/8" |
| HF-5 | 5/16" | 5/16" | 7/8" |
| Standard 1/2" Band 5/16" Screw | | | |
| HF-6 | 3/8" | 3/8" | 25/32" |
| HF-8 | 1/2" | 1/2" | 1" |
| HF-10 | 5/8" | 9/16" | 1 1/8" |
| HF-12 | 3/4" | 1 1/8" | 1 1/4" |
| HF-16 | 1" | 5/8" | 1 1/2" |
| HF-20 | 1 1/4" | 1 1/8" | 1 3/4" |
| HF-24 | 1 1/2" | 1 1/8" | 2" |
| HF-28/30 | 1 3/4" | 1 1/8" | 2 3/8" |
| HF-32 | 2" | 1 1/8" | 2 1/2" |
| HF-36 | 2 1/4" | 1 1/8" | 2 3/4" |
| HF-40 | 2 1/2" | 2 1/8" | 3" |
| HF-44 | 2 3/4" | 2 1/8" | 3 1/4" |
| HF-48 | 3" | 2 1/8" | 3 1/2" |
| HF-52 | 3 1/4" | 2 1/8" | 3 3/4" |
| HF-54 | 3 1/2" | 3" | 3 3/8" |
| HF-56 | 3 1/2" | 3" | 4" |
| HF-60 | 2 3/4" | 3 1/8" | 4 1/4" |
| HF-64 | 4" | 3 3/8" | 4 1/2" |
| HF-72 | 4 1/4" | 4 1/8" | 5" |
| HF-80 | 5" | 4 3/8" | 5 1/2" |
| HF-84 | 5 1/4" | 4 3/8" | 5 1/8" |
| HF-88 | 5 1/2" | 5 1/8" | 6" |
| HF-96 | 6" | 5 3/8" | 6 1/2" |
| HF-104 | 6 1/2" | 6 1/8" | 7" |
| HF-116 | 7 1/4" | 6 3/8" | 7 3/4" |
| HF-120 | 7 1/2" | 6 3/8" | 7 7/8" |
| HF-124 | 7 3/4" | 6 3/8" | 8 1/4" |
| HF-128 | 8" | 7 3/8" | 8 1/2" |
| HF-140 | 8 3/4" | 7 3/8" | 9 1/4" |
| HF-152 | 9 1/2" | 9 1/8" | 10" |
| HF-156 | 9 3/4" | 8 3/8" | 10 1/4" |
| HF-160 | 10" | 9 1/8" | 10 1/2" |
| HF-180 | 11 1/4" | 10 3/8" | 11 3/4" |
| HF-190 | 11 3/4" | 10 3/8" | 12 1/4" |
| HF-212 | 13 1/8" | 12 3/8" | 13 5/8" |
| HF-224 | 14" | 13 1/4" | 14 1/2" |

| No. | Size | Min. | Max. |
|---------------------------------|---------|---------|---------|
| Mini Clamp 3/8" Band 1/4" Screw | | | |
| HF-4-SS | 1/4" | 1/4" | 5/8" |
| HF-5-SS | 5/16" | 5/16" | 7/8" |
| Standard 1/2" Band 5/16" Screw | | | |
| HF-6-SS | 3/8" | 3/8" | 25/32" |
| HF-8-SS | 1/2" | 1/2" | 1" |
| HF-10-SS | 5/8" | 9/16" | 1 1/8" |
| HF-12-SS | 3/4" | 1 1/8" | 1 1/4" |
| HF-16-SS | 1" | 5/8" | 1 1/2" |
| HF-20-SS | 1 1/4" | 1 1/8" | 1 3/4" |
| HF-24-SS | 1 1/2" | 1 1/8" | 2" |
| HF-28/30-SS | 1 3/4" | 1 1/8" | 2 3/8" |
| HF-32-SS | 2" | 1 1/8" | 2 1/2" |
| HF-36-SS | 2 1/4" | 1 1/8" | 2 3/4" |
| HF-40-SS | 2 1/2" | 2 1/8" | 3" |
| HF-44-SS | 2 3/4" | 2 1/8" | 3 1/4" |
| HF-48-SS | 3" | 2 1/8" | 3 1/2" |
| HF-52-SS | 3 1/4" | 2 1/8" | 3 3/4" |
| HF-54-SS | 3 1/2" | 3" | 3 3/8" |
| HF-56-SS | 3 1/2" | 3" | 4" |
| HF-60-SS | 2 3/4" | 3 1/8" | 4 1/4" |
| HF-64-SS | 4" | 3 3/8" | 4 1/2" |
| HF-72-SS | 4 1/4" | 4 1/8" | 5" |
| HF-80-SS | 5" | 4 3/8" | 5 1/2" |
| HF-84-SS | 5 1/4" | 4 3/8" | 5 1/8" |
| HF-88-SS | 5 1/2" | 5 1/8" | 6" |
| HF-96-SS | 6" | 5 3/8" | 6 1/2" |
| HF-104-SS | 6 1/2" | 6 1/8" | 7" |
| HF-116-SS | 7 1/4" | 6 3/8" | 7 3/4" |
| HF-120-SS | 7 1/2" | 6 3/8" | 7 7/8" |
| HF-124-SS | 7 3/4" | 6 3/8" | 8 1/4" |
| HF-128-SS | 8" | 7 3/8" | 8 1/2" |
| HF-140-SS | 8 3/4" | 7 3/8" | 9 1/4" |
| HF-152-SS | 9 1/2" | 9 1/8" | 10" |
| HF-156-SS | 9 3/4" | 8 3/8" | 10 1/4" |
| HF-160-SS | 10" | 9 1/8" | 10 1/2" |
| HF-180-SS | 11 1/4" | 10 3/8" | 11 3/4" |
| HF-190-SS | 11 3/4" | 10 3/8" | 12 1/4" |
| HF-212-SS | 13 1/8" | 12 3/8" | 13 5/8" |
| HF-224-SS | 14" | 13 1/4" | 14 1/2" |

DISPLAY RACKS WITH GS SERIES

WRB-100-*



WRB-200-*



PART NO. WRB-200-CS

| No. | Quantity |
|-------|----------|
| HF-4 | 25 |
| HF-5 | 25 |
| HF-8 | 20 |
| HF-10 | 20 |
| HF-12 | 20 |
| HF-16 | 20 |
| HF-20 | 20 |
| HF-24 | 20 |
| HF-28 | 20 |
| HF-32 | 20 |
| HF-40 | 20 |
| HF-48 | 20 |
| HF-64 | 20 |

PART NO. WRB-200-SS

| No. | Quantity |
|----------|----------|
| HF-4-SS | 25 |
| HF-5-SS | 25 |
| HF-8-SS | 20 |
| HF-10-SS | 20 |
| HF-12-SS | 20 |
| HF-16-SS | 20 |
| HF-20-SS | 20 |
| HF-24-SS | 20 |
| HF-28-SS | 20 |
| HF-32-SS | 20 |
| HF-40-SS | 20 |
| HF-48-SS | 20 |
| HF-64-SS | 20 |

PART NO. WRB-100-CS

| No. | Quantity |
|-------|----------|
| HF-4 | 25 |
| HF-5 | 25 |
| HF-8 | 20 |
| HF-10 | 20 |
| HF-16 | 20 |
| HF-24 | 20 |

PART NO. WRB-100-SS

| No. | Quantity |
|----------|----------|
| HF-4-SS | 25 |
| HF-5-SS | 25 |
| HF-8-SS | 20 |
| HF-10-SS | 20 |
| HF-16-SS | 20 |
| HF-24-SS | 20 |